

規 格 書

SPECIFICATION

品名：

LED LAMP

PART NAME

料號：

MT-3NH4B(HTG)

PART NO :





洺辰科技有限公司

MENTOR TECHNOLOGIES CO., LTD.

新北市中和區中正路700號7樓-6

TEL:(02)8227-8556 FAX:(02)8227-8551

■ Package Dimension:



Part Number	Chip		Lens Color
	Material	Emitting Color	
MT-3NH4B(HTG)	InGaN	BLUE	Blue Diffused

■ Material List:

Item	Part No.
Lead Frame	2004S
Chip	CEBHV08A
Gold Wire	0.9mil
Silver Epoxy	DX-20CA-07
Epoxy	6671D/H592

■ NOTES:

- 1.All dimension are millimeters.
- 2.Tolerance is ± 0.25 mm unless otherwise noted.

1.SPECIFICATIONS (BLUE)						
(1) Absolute Maximum Rating				(Ta=25°C)		
Item	Symbol	Absolute Maximum Rating			Unit	
Forward Current	If	25			mA	
Peak Forward Current	Ifp	100			mA	
Reverse Voltage	Vr	5			V	
Power Dissipation	Pd	85			mW	
Electrostatic Discharge (HBM)	ESD	1500			V	
Operating Temperature	Top	-40°C~85°C			°C	
Storage Temperature	Tstg	-40°C~100°C			°C	
Lead Soldering Temperature	Tsol	260°C FOR 5 SECONDS				
IFP Conditions: Pulse Width≤0.1msec.and duty ≤1/10						
(2) Initial Electrical/Optical Characteristics				(Ta=25°C)		
Item	Symbol	Condition	Min	Typ	Max	Unit
Forward Voltage	Vf	If=20(mA)	2.7	3.1	3.6	V
Reverse Current	Ir	Vr=5(V)	/	/	10	μ A
Viewing Angle	2 θ 1/2	If=20(mA)	/	30	/	deg
Luminous Intensity	Iv	If=20(mA)	70	140	/	mcd
Peak Wavelength	λ p	If=20(mA)	460	465	470	nm
Dominant Wavelength	λ d	If=20(mA)	465	470	475	nm
Recommend Forward Current	IF(Rec)	/	/	20	/	mA
2.TYPICAL INITIAL OPICAL/ELECTRICAL CHARACTERISTICS						
Please refer to Figures : in Page 3						
3.OUTLINE DIMENSION AND MATERIALS						
Please refer to drawing: in Page 2						
Material as follows: Resin :Epoxy						
Lead frame:Ag plating Copper ally						
4.This paragraph is 150° TG high glue.						

3. Typical Electro-Optical Characteristic Curves: (BLUE)

Fig1. Forward Current vs. Forward Voltage




Fig2. Relative Intensity vs. Forward Current




Fig3. Forward Voltage vs. Temperature




Fig4. Relative Intensity vs. Temperature






Fig5. Relative Intensity vs. Wavelength



Radiation Diagram $T_a=25^\circ\text{C}$



RADIATION DIAGRAM

4.Rreliability Performance					
(1)Reliability test item and condition					
NO	Item	Test Conditions	Test Hours/Cycle	Sample Size	Ac/Re
1	Solder Heat	TEMP:260±5°C	5 SEC	76pcs	0/1
2	Temperature Cycle	H:+85°C 30min δ 5min L:-40°C 30min	50CYCLE	76pcs	0/1
3	Thermal Shock	H:+100°C 5min δ 10sec L:-10°C 5min	50CYCLE	76pcs	0/1
4	High Temperature Storage	TEMP:100°C	1000HRS	76pcs	0/1
5	Low Temperature Storage	TEMP:-40C	1000HRS	76pcs	0/1
6	DC Operating Life	If=20mA	1000HRS	76pcs	0/1
7	High Temperature High Humidity	85°C/85%RH	1000HRS	76pcs	0/1
(2)CRITERIA FOR JUDGING THE DAMAGE					
		Test Conditions	Criteria for judgement		
			Min	Max	
Voltage(Forward)	VF	IF=20mA	-	U.S.L*)×1.1	
Current(Reverse)	IR	VR=5V	-	U.S.L*)×2.0	
Luminous Intensity	IV	IF=20mA	L.S.L**)×0.7	-	
*)U.S.L.: Upper Standard Level. **)L.S.L.:Lower Standard Level.					