

規 格 書

SPECIFICATION

品名：

LED LAMP

PART NAME

料號：

MT-3N4G(HTG)

PART NO :




洺辰科技有限公司

MENTOR TECHNOLOGIES CO., LTD.

新北市中和區中正路700號7樓-6

TEL:(02)8227-8556 FAX:(02)8227-8551

■ Package Dimension:



Part Number	Chip		Lens Color
	Material	Emitting Color	
'OV/5P 6I *J VI +	GaP	GREEN	Green Diffused

■ Material List:

Item	Part No.
Lead Frame	2004S
Chip	108YGK
Gold Wire	0.9mil
Silver Epoxy	TMT-354-TP
Epoxy	6671D/H592

■ NOTES:

- 1.All dimension are millimeters.
- 2.Tolerance is ± 0.25 mm unless otherwise noted.

"

"

1.SPECIFICATIONS						
(1) Absolute Maximum Rating				(Ta=25°C)		
Item	Symbol	Absolute Maximum Rating		Unit		
Forward Current	If	20		mA		
Peak Forward Current	Ifp	100		mA		
Reverse Voltage	Vr	5		V		
Power Dissipation	Pd	80		mW		
Electrostatic Discharge (HBM)	/	/		V		
Operating Temperature	Top	-40°C~80°C		°C		
Storage Temperature	Tstg	-40°C~100°C		°C		
Lead Soldering Temperature	Tsol	260°C FOR 5 SECONDS				
IFP Conditions: Pulse Width ≤ 0.1msec. and duty ≤ 1/10						
(2) Initial Electrical/Optical Characteristics				(Ta=25°C)		
Item	Symbol	Condition	Min	Typ	Max	Unit
Forward Voltage	Vf	If=20(mA)	1.9	2.2	2.8	V
Reverse Current	Ir	Vr=5(V)	/	/	10	μ A
Viewing Angle	2 θ 1/2	If=20(mA)	/	35	/	deg
Luminous Intensity	Iv	If=20(mA)	5	10	/	mcd
Peak Wavelength	λ p	If=20(mA)	560	565	570	nm
Dominant Wavelength	λ d	If=20(mA)	565	570	575	nm
Recommend Forward Current	IF(Rec)	/	/	10~20	/	mA
2.TYPICAL INITIAL OPICAL/ELECTRICAL CHARACTERISTICS						
Please refer to Figures : in Page 3						
3.OUTLINE DIMENSIONS AND MATERIALS						
Please refer to drawing: in Page 2						
Material as follows: Resin :Epoxy						
Lead frame:Ag plating Copper ally						

3. Typical Electro-Optical Characteristic Curves:

Fig1. Forward Current vs. Forward Voltage




Fig2. Relative Intensity vs. Forward Current




Fig3. Forward Voltage vs. Temperature




Fig4. Relative Intensity vs. Temperature






Fig5. Relative Intensity vs. Wavelength



Radiation Diagram $T_a=25^\circ\text{C}$



"

"

4.Reliability Performance					
(1)Reliability test item and condition					
NO	Item	Test Conditions	Test Hours/Cycle	Sample Size	Ac/Re
1	Solder Heat	TEMP:260±5℃	5 SEC	76pcs	0/1
2	Temperature Cycle	H:+85℃ 30min δ 5min L:-40℃ 30min	50CYCLE	76pcs	0/1
3	Thermal Shock	H:+100℃ 5min δ 10sec L:-10℃ 5min	50CYCLE	76pcs	0/1
4	High Temperature Storage	TEMP:100℃	1000HRS	76pcs	0/1
5	Low Temperature Storage	TEMP:-40℃	1000HRS	76pcs	0/1
6	DC Operating Life	If=20mA	1000HRS	76pcs	0/1
7	High Temperature High Humidity	85℃/85%RH	1000HRS	76pcs	0/1
(2)CRITERIA FOR JUDGING THE DAMAGE					
		Test Conditions	Criteria for judgement		
			Min	Max	
Voltage(Forward)	VF	IF=20mA	-	U.S.L*)×1.1	
Current(Reverse)	IR	VR=5V	-	U.S.L*)×2.0	
Luminous Intensity	IV	IF=20mA	L.S.L**)×0.7	-	
*)U.S.L.: Upper Standard Level. **)L.S.L.:Lower Standard Level.					